



Automatic Shrink-Wrap Packaging Machine (Overlap)



Specifications	Model	FYT-501	FYT-501 Overlapping Tray Shrink
Item		Overlapping Machine	Shrinking Tunnel
Voltage		220V x 3 ; 60 Hz	220V x 3 ; 60 Hz
Hp		6 Hp	2 Hp
Heat			32 KW
Air Consumption		5-6 kgf/cm2 100n/min	
Packing Speed		20-30 Packs/min	5-25 m/min
Shrink Film (LDPE)		Transparent or printed film	Transparent or printed film
Packing Size		(LxWxD) Unit:mm) 300-420 Lx200-400Wx140-330H	(LxWxD) Unit:mm) MAX : 420Lx400Wx350H
Machine Dimension (LxWxH)		2800Lx1190Wx1450H Unit:mm)	2800Lx1330Wx1810H Unit:mm)
Operation Height		950+ 50mm H	950+ 50mm H
Machine Weight		1000kgs	900kgs

Specifications	Model	High Speed Overlapping Packing Machine	
Item		Packing Machine	Shrink Tunnel
Power		220V x 3 50/60Hz	220V x 3 50/60Hz
Hp		7 Hp	Electric Heating 23 KW
Air Pressure		5-6 kgf/cm2	
Packing Capacity		2x3 480	5-15 m/min
Film applied		PE Transparent or colorful printing film	PE Transparent or colorful printing film
Effective packing size (LxWxH)		250 x 200 x 350 mm	350 x 270 x 300 mm
Machine dimension (LxWxH)		3000 x 1200 x 2200 mm	4000 x 1200 x 2180 mm
Machine weight		1000 kg	1000 kg

